

Despatch note for regrind articles

Drills, NC spot drills and stepped drills



Drills are reground on the main cutting edges and coated with original coating if possible.
Drills are reduced depending on the amount of wear and ground as new.
Stepped drills are also ground on the countersink angle.

Standard process			Main cutting edge + Chamfer if required + Original coating	Customer request Comment
Position	Article No. (New article)	No. of pieces		
1			<input checked="" type="checkbox"/>	
2			<input checked="" type="checkbox"/>	
3			<input checked="" type="checkbox"/>	
4			<input checked="" type="checkbox"/>	
5			<input checked="" type="checkbox"/>	
6			<input checked="" type="checkbox"/>	
7			<input checked="" type="checkbox"/>	
8			<input checked="" type="checkbox"/>	
9			<input checked="" type="checkbox"/>	
10			<input checked="" type="checkbox"/>	
11			<input checked="" type="checkbox"/>	
12			<input checked="" type="checkbox"/>	
13			<input checked="" type="checkbox"/>	
14			<input checked="" type="checkbox"/>	
15			<input checked="" type="checkbox"/>	

i If a regrind is not economically viable, your tools will be returned unprocessed.

Company	Department
Street	Contact
Post code / town	Contact Tel. No.
Customer No. (if known)	Your order number



i Download → www.wnt.com/uk/download

03/2018